

The background of the entire page is a close-up, angled view of a network switch or patch panel. It features rows of blue RJ45 ports with yellow Ethernet cables plugged in. The lighting is dramatic, with a bright yellow and blue glow emanating from the center, creating a sense of energy and connectivity. The Prolink logo is positioned in the top left corner.

PROLINK

We provide our customers with exceptional PRODUCTS in accordance with the highest international standards and also provide SERVICES that meets our customers' needs or exceeds their expectations.

Powered by:  PROLINK

Discription

ProLink Single ARMOR CENTRAL LOOSE TUBE CABLE 12-CORE SM 9/125 PER METER OD:10MM

Items		Unit	Specifications 9/125
Cladding Diameter		μm	124.8±0.7
Core Non-Circularity		%	≤0.7
Core-Cladding Concentricity Error		μm	≤0.5
Coating Diameter		μm	245±5
Coating Non-Circularity		%	≤6.0
Cladding-Coating Concentricity Error		μm	≤12.0
Cable Cutoff Wavelength		nm	λ _{cc} ≤1260
Mode Field Diameter	1310nm	μm	9.2±0.4
	1550nm	μm	10.4±0.5
Attenuation (max.)	1310nm	dB/km	≤0.36
	1550nm	dB/km	≤0.22

Cable Parameter

Fiber Count	Speci cations	
Fiber Count	24	
Colored Coating Fiber	Dimension	250μm±15μm
	Color	Blue, orange, green, brown, gray, natural color, Red, black, yellow, purple, pink, aqua blue
Loose Tube	Dimension	2.0mm±0.5mm
	Material	PBT
	Tube color	Blue, orange, green, brown
	Loose tube number	1
	Filling rope number	1
Material of reinforcement	Fiber in loose tube number 24	
	Phosphating steel wire 1.0mm	
Outer / Inner Jacket	Dimension	Inner1.6mm±0.10mm/Outer1.7mm±0.10mm
	Material	HDPE
	Sheath color	Black
	Line color	Yellow
Flame retardant		
Sheath outer diameter:	10mm±0.2mm	

Mechanical and Environmental Characteristics

Items	Unit	Speci cations
Tension (Long Term)	N	600
Tension (Short Term)	N	1500
Crush (Long Term)	N/100mm	300
Crush (Short Term)	N/100mm	1000
Min. Bend Radius (Dynamic)	mm	20D
Min. Bend Radius (Static)	mm	10D
Installation Temperature	°C	-20~+60
Operating Temperature	°C	-40~+70
Storage Temperature	°C	-40~+70
Standard	IEC, EIA/TIA 455	
Fracture elongation of sheath	≥350	
Tensile strength of sheath	12.0Mpa	