


The Prolink logo features the word "PROLINK" in a bold, white, sans-serif font. A white, curved line arches over the letters "O" and "L", and another white, curved line arches under the letters "I" and "N".

# PROLINK

A close-up, low-angle shot of a network switch or patch panel. The device is a light-colored metal rack-mountable unit. It features multiple rows of blue RJ45 ports and fiber optic ports. Several yellow fiber optic cables are plugged into the ports. The scene is dramatically lit with a strong blue and yellow light source, creating a high-contrast, futuristic atmosphere. The background is dark, making the illuminated components stand out.






We provide our customers with exceptional PRODUCTS in accordance with the highest international standards and also provide SERVICES that meets our customers' needs or exceeds their expectations.

Powered by: The Prolink logo, consisting of the word "PROLINK" in a bold, white, sans-serif font, with a white, curved line arching over the "O" and "L", and another white, curved line arching under the "I" and "N".

## Discription




ProLink F/O JUMPER CORD ,LC -LC-MM DUPLEX – OM4 5M

## Features

-  Small Size, High Precision.
-  Zirconia 1.25mm ceramics ferrule.
-  Low insertion Loss.
-  High Return Loss.
-  Duplex are Available.



## Applications

-  Telecom and Datacom Equipment.
-  LAN/WAN
-  Device Terminals

## Speciation's

<b>Connectors type</b>	LC-LC
<b>Cable</b>	OM4 Duplex 5M
<b>Fiber Type</b>	OM4 50/125
<b>Cable Color</b>	Fuchsia
<b>insertion loss</b>	≤0.25 dB
<b>return loss</b>	≥30dB
<b>joint endurance</b>	>1000Times
<b>Operating Temperature</b>	-40°C~+70°C
<b>Storage Temperature</b>	-25°C~+60°C
<b>ROHS</b>	Meet 2002/95/EC Requirement