PRORACK
Powered by PROLINK

We provide customers with satisfactory products and services according to international standards, to meet different customer needs.

Pro-Rack is powered by: **PROLINK**

Description:

Standing network rack with glass door, 4 fans, 1 shelf and 1 PDU 8 outlet.

Main material:

Cold-rolled steel.

Load capacity:

Static load: 800KG.

Surface treatment:

Degreasing, pickling, phosphating, laundering, powder coating.

Features:

- Exquisite design with precise dimensions and craftsmanship.
- Two side panels for each side can be separately open with locks, which are easy to operation and maintenance.
- Two back sides with multifunctional cable routing panels.
- High-class locks.
- Casters and support feet can be installed simultaneously.
- Optional pedestals for fixation, cable routing, ventilation, and rat proof.
- Curved front screen door & back double screen door enable equipment to ventilate well.
- Various optional accessories.
- Pro-Rack logo is printed on the side panel.

1

Structure

1. Top cover
2. Bottom plate
3. Fans
4. Frame
5. Front door
6. Back door
7. Side panel
8. Horizontal bracket
9. Profile rails
10. Shelf
11. Caster
12. Support foot

Size

back   side   front   side(with no side panel on)

cover

cable routing rabbet

cable manager

Pro-Rack is powered by: PROLINK

Installing

Package A (top cover, bottom plate, shelf, horizontal bracket, accessories)

Package B (front/back doors, side panels, frames, profile rails, fans)

Pro-Rack is powered by: PROLINK

Technical parameters:

NANES	QUANTITY	UNIT	MATERIALS	SURFACE TREATMENT	REMARKS
Top Covers	1	Pc	1.2mm cold-rolled steel	powder coating	
Bottom plates	1	Pc	1.2mm cold-rolled steel	powder coating	
Fans	4	Pc	1.2mm cold-rolled steel	powder coating	
Frames	2	Pc	1.2mm cold-rolled steel	powder coating	
Front doors	1	Pc	5mm tempered glasses 1.2mm cold-rolled quality steel	powder coating	door type E or B
Back doors	1	Pc	1.2mm cold-rolled steel	powder coating	door type K
Side panels	2	Pc	1.0mm cold-rolled steel	powder coating	
Rails	4	Pc	2.0mm cold-rolled steel	powder coating	
Shelves	1	Pc	1.2mm cold-rolled steel	powder coating	
Casters	4	Pc			
M12 support feet	4				
Cage nuts	40				
Sockets with 8 outlet	1				
Beams	6	Pc	1.2mm cold-rolled steel	powder coating	
Junction boxes	12	Pc	2.0mm cold-rolled steel		

TYPES	PR-FG6827
CAPACITY (U)	27U
WIDTH	600
DEPTH	800
HEIGHT	1388
WHOLE PACKAGE	
WIDTH	620
DEPTH	820
HIGHT	1398
VOLUME (M^3)	0.597
FLAT PACKAGE	
PACKAGE A	1320*620*320
PACKAGE B	1020*620*130
PACKAGE C	
VOLUMES (M^3)	0.328
Front Door	Glass

Color:

   BLACK (RAL9005)